

SYSTEM WITH FFV DECK



HPVIDEO 2 Camera System, with FFV 2 Channel Deck. Perfect for Recording and Playback, for all Existing Cametas, SDI, HD-SDI and 3G-SDI Signals.

Rating: Not Rated Yet

[Ask a question about this product](#)

SYSTEM WITH FFV DECK

Description

HD 2 CAMERA SYSTEM INCLUDES:

1. [2 X 17" PANASONIC LCD MONITORS WITH BRACKETS AND HPVIDEO SINGLE CABLE MOD'S](#)
2. [2 X 20" JVC LCD MONITORS WITH BRACKETS AND HPVIDEO SINGLE CABLE MOD'S](#)
3. 5 X 100FT MULTI PIN CABLE
4. 5 X 100FT BNC CABLE (1505F BY BELDEN)
5. [HD VIDEO ASSIST CART](#)
 - OPERATOR HD MONITORS (2 X 7" 3G HD-SDI MONITORS)
 - 2 CHANNEL HD-SDI HARD DRIVE RECORDER
 - HD-SDI AUDIO VIDEO CONTROLLER BOX
 - B/W VIDEO PRINTER

SPECIFICATIONS:

HD VIDEO ASSIST CART

- AC POWER RANGE FROM 100-240V
- 2 HD-SDI VIDEO INPUTS (A AND B CAMERAS)
- LOOP THRU OUTPUTS FOR EACH CAMERA INPUTS
- 1 X 3 PIN XLR ANALOGUE AUDIO INPUT
- 2 X ANALOGUE AUDIO AND 3 X HD-SDI DVR AUX OUTPUTS FOR EACH DVR RECORDERS
- 2 X RS232 CONNECTORS FOR EXTERNAL CONTROL
- A,B LIVE AND A,B DVR PLAYBACK OUTPUTS FOR OPERATOR MONITORS
- A AND B NTSC DVR OUTPUTS FOR SONY B/W VIDEO PRINTER OR ANY NTSC MONITOR
- INDEPENDENT ANALOGUE AUDIO OR EMBEDDED AUDIO AND HD-SDI VIDEO RECORDING
- OPERATOR SPEAKER VOLUME CONTROL
- A,B PLAYBACK AUDIO AND INTERCOM OPERATOR SWITCH
- EXTERNAL SPEAKER VOLUME CONTROL
- 4 X MULTI PIN OUTPUT CONNECTORS FOR EXTERNAL MONITORS (WITH HPVIDEO SINGLE CABLE MOD'S)
- A,B PLAYBACK EXTERNAL AUDIO OR INTERCOM SWITCH (INDEPENDENT PLAYBACK AND LIVE VIDEO SWITCH'S) FOR EVERY MULTI PIN OUTPUT CONNECTORS FOR EXTERNAL MONITORS
- ACCEPTS FOUR MODES:
 - CHANNEL A LIVE
 - CHANNEL A PLAYBACK
 - CHANNEL B LIVE
 - CHANNEL B PLAYBACK
- MONITORS (WITH HPVIDEO SINGLE CABLE MOD'S)
- CAN BE DAISY CHAINED (1 CABLE SUPPORTS 2 MONITORS)
- BUILT-IN FULL INTERCOM SYSTEM
- EXTERNAL MIC'S SELECTING SWITCH'S
- 12V 20 AMP DC OUTPUT
- BUILT IN ANALOGUE AUDIO OR EMBEDDED AUDIO AND HD-SDI VIDEO RECORDER DECK (FROM FFV)
- SUPPORTED RESOLUTIONS: 1080i/60/59.94/50/24 psf
 - (1920 x 1080/60/59.94/50/2:1 Interlace)
 - 1080s/23.98/24.00 (PSF)
 - 720p/60/59.94/50
 - (1280 x 720/60/59.94/50/Progressive)
 - 720p/23.98/24.00
 - NTSC (720 x 486/59.94/2:1 Interlace)
 - PAL (720 x 576/50/2:1 Interlace)
 - SUPPORTS 4:3 or 16:9 ASPECT RATIO
- SONY B/W VIDEO PRINTER
- RACK MOUNT OPERATOR MONITORS
- OPERATORS MONITORS INDIVIDUAL CONTROL (LIVE OR DVR)
- COMPATIBLE INPUT FORMATS FOR OPERATOR MONITORS:
 - 480p / 59.94 576p/50
 - 720p / 60/ 59.94/50/30/29.97/25
 - 1035i / 60/59.94
 - 1080i / 60/59.94/50
 - 1080psF / 24/23.98
 - 1080p / 30/29.97/25/24/23.98
 - 3G-Formats **
 - 3G-SDI
 - 1080p / 60/59.94/50
- AND MORE...

- EXTERNAL MONITORS (WITH HPVIDEO SINGLE CABLE MOD'S)
- 17" PANASONIC LCD MONITOR
MODEL # BT-LH1710W
EVERY EXTERNAL MONITOR MODIFIED WITH BRACKET AND SINGLE CABLE MOD'S
(MONITOR POWER, INTERCOM MIC, SPEAKER AND HD-SDI VIDEO)
- 20" JVC LCD MONITOR
MODEL # DT-V20L1DU
EVERY EXTERNAL MONITOR MODIFIED WITH BRACKET AND SINGLE CABLE MOD'S
(MONITOR POWER, INTERCOM MIC, SPEAKER AND HD-SDI VIDEO)
- MULTI PIN CABLE
100FT HIGH FLEX PRECISION MULTI PIN CABLE
(MONITOR POWER, INTERCOM MIC, SPEAKER AUDIO AND HD-SDI VIDEO)
BY USING BARRELS YOU CAN EXTEND UP TO 200FT