

HP7007



2.4Ghz 8 Camera Microwave Handheld monitor and Transmitter System

Rating: Not Rated Yet

[Ask a question about this product](#)

Description

HANDHELD MONITOR/TRANSMITTER

MICROWAVE HANDHELD MONITOR:

- SCREEN SIZE: 7 INCHES DIGITAL
- RATIO:15:9 WIDE TFT SCREEN
- RESOLUTION: 800x480
- DOT RESOLUTION: 2400 x 480 (= 1,152,000 dots)
- COLOR CONFIGURATION: RGB STRIPE
- VIDEO SYSTEM: PAL/NTSC
- BUILT-IN MICROWAVE AV RECEIVER
- NORMAL FULL SCREEN MODES
- LOW REFLECTION LCD PANEL
- ADJUSTABLE BACKLIGHT CONTROL
- VIDEO LINE INPUT(RCA FOR AUDIO AND BNC FOR VIDEO)
- TUNER VIDEO OUTPUT(RCA FOR AUDIO AND BNC FOR VIDEO)
- 8 CHANNELS (SELECTABLE)
- OPERATES ON SONY NP "L" OR "M" SIZE BATTERY (2-3HRS)
- DC POWER INPUT 12V 4 PIN XLR CONNECTOR
- FULL PICTURE CONTROL MENU (COLOR BRIGHTNESS,CONTRAST ANT TINT)
- VOLUME CONTROL
- INPUT CONTROL (RECEIVER OR LINE INPUT)
- SMA TYPE ANTENNA INPUT CONNECTOR
- 2.5 MM HEADPHONE JACK FOR AUDIO MONITORING
- DIMENSIONS 7.4:1 (WHD)

MICROWAVE AV TRANSMITTER:

- PAL OR NTSC COLOR SYSTEM
- AV INPUT (BNC, RCA)
- HIROSE 8-PIN POWER CONNECTOR
- HIROSE CONNECTOR PINOUTS:
 - PIN #1 GROUND
 - PIN#2 VIDEO IN
 - PIN #3 DC POWER IN
 - PIN#4 AC GROUND
 - PIN #5 DC POWER IN
 - PIN #6 AUDIO IN
- COMPATIBLE WITH ALL MODULUS CAMERA POWER CABLES
- OPERATES 9 TO 36V DC
- WIRELESS POWER OUTPUT 1W
- 8 CHANNELS (SELECTABLE)
- CHANNELS FREQUENCIES
 - CH 1 2480 MHZ
 - CH 2 2390 MHZ
 - CH 3 2370 MHZ
 - CH 4 2470 MHZ
 - CH 5 2450 MHZ
 - CH 6 2430 MHZ
 - CH 7 2410 MHZ
 - CH 8 2510 MHZ
- SMA TYPE CONNECTOR FOR ANTENNA
- OPERATING RANGE 500-700FT
- DIMENSIONS 2": 3": 0.6" (WHD)

Price \$1500.00

RELATED VIDEOS