

## FFV BRIEFCASE



Rating: Not Rated Yet

[Ask a question about this product](#)

Description

### HD DUAL-CAMERA PORTABLE HDD RECORDER/BRIEFCASE SPECIFICATION

- AC POWER RANGE FROM 100-240V
- DC POWER RANGE FROM 10-20V
- 4 PIN XLR CONNECTOR FOR DC INPUT
- 2 X HD OPERATOR MONITORS (A & B CAMERAS) WITH INDIVIDUAL CONTROL (LIVE OR DVR)
- COMPATIBLE INPUT FORMATS FOR OPERATOR MONITORS:
  - 480p / 59.94 576p/50
  - 720p / 60/ 59.94/50/30/29.97/25
  - 1035i / 60/59.94
  - 1080i / 60/59.94/50
  - 1080psF / 24/23.98
  - 1080p / 30/29.97/25/24/23.98
  - 3G-Formats \*\*
  - 3G-SDI
  - 1080p / 60/59.94/50
- 2 X OPERATOR SPEAKERS
- 4W EACH SPEAKER
- HEADPHONE CONNECTOR (MUTING THE SPEAKER,WHEN IT IS IN USE)

- 2 X HD-SDI INPUTS (A & B CAMERAS), BNC CONNECTORS
- 1 X 3PIN XLR ANALOG AUDIO INPUT
- 2 X MULTIPIN MONITOR OUTPUTS, (POWER,AUDIO,VIDEO,INTERCOM), FOR HPVIDEO SINGLE CABLE MOD'S
- 2 X HD-SDI OUTPUTS FOR EACH DVR,BNC CONNECTORS
- 1 X ANALOG AUDIO OUTPUT PER CHANNEL,RCA CONNECTORS
- 2 X TIME CODE RECORDING
- BUILT IN ANALOGUE AUDIO OR EMBEDDED AUDIO AND HD-SDI VIDEO DUAL CHANNEL RECORDER:
  - FRONT PANEL TOUCH SCREEN CONTROL
  - RS-232 MACHINE CONTROL
  - RECORDS JPEG2000.mov FILE IN HD OR SD
  - DATA RATES UP TO 100 Mbit/s PER CHANNEL
  - 4:2:2 SAMPLING
  - 10 BIT QUANTIZATION
  - 8 EMBEDDED AUDIO CHANNELS PER HD VIDEO CHANNEL
  - 4 EMBEDDED AUDIO CHANNELS PER SD VIDEO CHANNEL
  - CONFORMS TO INDUSTRY DIGITAL SPECIFICATION SMPTE 259M-C AND SMPTE 292(HD-SDI)
  - SMPTE/EBU LONGITUDINAL TIME CODE
  - CHASE LOCK
  - DISCRETE ACCESS TO EVERY FRAME
  - LOOP RECORD FEATURE
  - INSTANT CUEING,CLIP RECALL
  - PLAY LIST MANAGEMENT ANDCLIP NAMING FROM THE FRONT PANEL
  - DYNAMIC TRACKING
  - VARIABLE SPEED NOISE-FREE PLAYBACK FORWARD AND REVERSE
  - 2 X REMOVABLE HARD DRIVE'S
  - CAPABLE OF UP TO 9 HOURS OF RECORD TIME ON 500GB HARD DRIVE
- FULL INTERCOM SYSTEM
- A,B PLAYBACK AUDIO AND INTERCOM OPERATOR SWITCH
- OPERATOR SPEAKER VOLUME CONTROL
- A,B PLAYBACK EXTERNAL AUDIO OR INTERCOM SWITCH
- EXTERNAL SPEAKER VOLUME CONTROL
- PLAYBACK AND LIVE VIDEO SWITCH'S FOR EVERY MULTI PIN OUTPUT CONNECTORS FOR EXTERNAL MONITORS,WITH HPVIDEO SINGLE CABLE MOD'S. ACCEPTS FOUR MODES:
  - CHANNEL A LIVE
  - CHANNEL A PLAYBACK
  - CHANNEL B LIVE
  - CHANNEL B PLAYBACK
- BRIEFCASE SUPPORTED RESOLUTIONS:
  - 1080i/60/59.94/50/24 psf
  - 1080psf/23.98/24.00 (PSF)
  - 720p/60/59.94/50
  - 720p/23.98/24.00
  - 576i/50.00
  - 480i/59.94
  - NTSC (720 x 486/59.94/2:1 Interlace)
  - PAL (720 x 576/50/2:1 Interlace)
- SUPPORTS 4:3 or 16:9 ASPECT RATIO
- EXTERIOR DIMENSIONS: 19.87" x 13.93" x 4.68"(50.4 x 35.4 x 11.9 cm)

RELATED VIDEOS