

QTAKE BRIEFCASE



Rating: Not Rated Yet

[Ask a question about this product](#)

Description

HD DUAL-CAMERA PORTABLE QTAKE SYSTEM / BRIEFCASE SPECIFICATION:

- AC POWER RANGE FROM 100-240V
- DC POWER RANGE FROM 10-20V
- 4 PIN XLR CONNECTOR FOR DC INPUT
- BUILT IN LAPTOP CHARGER, IT CHARGES THE LAPTOP ON AC AND DC MODE

- OPERATOR SPEAKER
- HEADPHONE CONNECTOR (MUTING THE SPEAKER,WHEN IT IS IN USE)
- 2 X HD-SDI INPUTS (A & B CAMERAS), BNC CONNECTORS
- 2 X HD-SDI OUTPUTS (A & B CAMERAS), BNC CONNECTORS
- 1 X 3PIN XLR ANALOG AUDIO INPUT
- 4 X MULTIPIN MONITOR OUTPUTS, (POWER,AUDIO,VIDEO,INTERCOM), FOR HPVIDEO SINGLE CABLE MOD'S
- 2 X HD-SDI OUTPUTS FOR EACH DVR,BNC CONNECTORS
- 1 X ANALOG, LINE LEVEL AUDIO OUTPUT PER CHANNEL,RCA CONNECTORS
- 4 X SD OUTPUTS, 2 X FOR A SIDE AND 2 X FOR B SIDE ,BNC CONNECTORS
- FULL INTERCOM SISTEM
- A,B PLAYBACK AUDIO AND INTERCOM OPERATOR SWITCH
- OPERATOR SPEAKER VOLUME CONTROL
- A,B PLAYBACK EXTERNAL AUDIO OR INTERCOM SWITCH
- EXTERNAL SPEAKER VOLUME CONTROL
- INCOMING AUDIO LEVEL CONTROL
- PLAYBACK AND LIVE VIDEO SWITCH'S FOR EVERY MULTI PIN OUTPUT CONNECTORS FOR EXTERNAL MONITORS,WITH HPVIDEO SINGLE CABLE MOD'S.
- BRIEFCASE SUPPORTED RESOLUTIONS:
 - 1080i/60/59.94/50/24 psh
 - 1080psf/23.98/24.00 (PSF)
 - 720p/60/59.94/50
 - 720p/23.98/24.00
- FULL TEMPERATUR CONTROL, WITH OLED SCREEN
- BUILT IN AUDIO DELAY BOX
- EXTERIOR DIMENSIONS: 19.87" x 13.93" x 4.68"(50.4 x 35.4 x 11.9 cm)